

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.	
09/835,821	04/17/2001	Jari Eikkula	P 280240 2010319US/HS/kop	5540	
909	7590 10/04/2005		EXAM	INER	
PILLSBUF	RY WINTHROP SHAV	MAIS, MARK A			
P.O. BOX 10500 MCLEAN, VA 22102			ART UNIT	PAPER NUMBER	
			2664		
			DATE MAILED: 10/04/2005		

Please find below and/or attached an Office communication concerning this application or proceeding.

		U				
		Application No.	Applicant(s)			
Office Action Summary		09/835,821	EIKKULA, JARI			
		Examiner	Art Unit			
		Mark A. Mais	2664			
Period fo	The MAILING DATE of this communication apport Reply	pears on the cover sheet with the	e correspondence address			
WHIC - Exte after - If NO - Failu Any	ORTENED STATUTORY PERIOD FOR REPLICED FOR REPLICED IN A CONTRESS CONTREST CONTRESS CONTREST CONTRESS CONTREST CONTRESS C	ATE OF THIS COMMUNICATION 36(a). In no event, however, may a reply be will apply and will expire SIX (6) MONTHS from the course the application to become ABANDO	ON. timely filed om the mailing date of this communication. NED (35 U.S.C. § 133).			
Status						
1)⊠	Responsive to communication(s) filed on Sept	tember6, 2001.				
2a)□	This action is FINAL . 2b)⊠ This action is non-final.					
3)						
	closed in accordance with the practice under E	Ex parte Quayle, 1935 C.D. 11,	453 O.G. 213.			
Disposit	ion of Claims					
4)⊠	Claim(s) 1-43 is/are pending in the application	l .				
	4a) Of the above claim(s) is/are withdrawn from consideration.					
5)□	5) Claim(s) is/are allowed.					
· —	6)⊠ Claim(s) <u>1-43</u> is/are rejected.					
·	Claim(s) is/are objected to.		•			
8)[_]	Claim(s) are subject to restriction and/o	or election requirement.				
Applicat	ion Papers					
9)🖂	The specification is objected to by the Examine	er.				
10)⊠	The drawing(s) filed on 17 April 2001 is/are: a) $□$ accepted or b) $⊠$ objected t	o by the Examiner.			
	Applicant may not request that any objection to the	drawing(s) be held in abeyance. S	See 37 CFR 1.85(a).			
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).						
11)	The oath or declaration is objected to by the Ex	xaminer. Note the attached Office	ce Action or form PTO-152.			
Priority (under 35 U.S.C. § 119					
	Acknowledgment is made of a claim for foreign ☐ All b)☐ Some * c)☐ None of:	n priority under 35 U.S.C. § 119	(a)-(d) or (f).			
1. Certified copies of the priority documents have been received.						
2. Certified copies of the priority documents have been received in Application No						
	3. Copies of the certified copies of the prior		ived in this National Stage			
	application from the International Burea					
* See the attached detailed Office action for a list of the certified copies not received.						
	•					
Attachmen	ot(s)					
1) Notice of References Cited (PTO-892) 4) Interview Summary (PTO-413) Notice of Draftsperson's Patent Drawing Review (PTO-948) Paper No(s)/Mail Date						
	ce of Draftsperson's Patent Drawing Review (PTO-948) mation Disclosure Statement(s) (PTO-1449 or PTO/SB/08)	5) Notice of Informa	Date Il Patent Application (PTO-152)			
	er No(s)/Mail Date <u>9/5/2002</u> .	6)				

DETAILED ACTION

Information Disclosure Statement

1. The information disclosure statement (IDS) submitted on September 5, 2002 was filed after the mailing date of the Application on April 17, 2001. The submission is in compliance with the provisions of 37 CFR 1.97. Accordingly, the examiner considered the information disclosure statement.

Drawings

2. The drawings are objected to under 37 CFR 1.83(a) because they fail to show "T_CSCF" as described in the specification. Any structural detail that is essential for a proper understanding of the disclosed invention should be shown in the drawing. MPEP § 608.02(d). Corrected drawing sheets in compliance with 37 CFR 1.121(d) are required in reply to the Office action to avoid abandonment of the application. Any amended replacement drawing sheet should include all of the figures appearing on the immediate prior version of the sheet, even if only one figure is being amended. The figure or figure number of an amended drawing should not be labeled as "amended." If a drawing figure is to be canceled, the appropriate figure must be removed from the replacement sheet, and where necessary, the remaining figures must be renumbered and appropriate changes made to the brief description of the several views of the drawings for consistency. Additional replacement sheets may be necessary to show the renumbering of the remaining figures. Each drawing sheet submitted after the filing date of an application must be labeled in the top margin as either "Replacement Sheet" or "New Sheet" pursuant to 37 CFR

1.121(d). If the changes are not accepted by the examiner, the applicant will be notified and informed of any required corrective action in the next Office action. The objection to the drawings will not be held in abeyance.

Specification

3. In the alternative, the disclosure is objected to because of the following informalities: It repeated refers to "T_CSCF", but Fig. 1, refers to "S_CSCF". Appropriate correction is required.

Claim Rejections - 35 USC § 102

4. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

- (b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.
- (e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.
- 5. Claims 1-18 and 21-36 are rejected under 35 U.S.C. 102(e) as being anticipated by Syrjala et al. (WO 01/91445).

6. With regard to claim 1, Syrjala et al. discloses a method for providing a network node with service reference information [CAMEL architecture, page 5, lines 7-9] in an IP-based system using an IP telephony signaling protocol [SIP or H.323, page 5, lines 32-33], wherein the method comprises the steps of:

Page 4

adding service reference information to an IP telephony signaling protocol message [adding global billing identifier, page 13, line 30-36; the billing identifier is a new parameter, page 14, lines 9-10], and

sending the IP telephony signaling protocol message to the network node [messages are sent over IP, page 10, lines 6-8].

- 7. With regard to claim 2, Syrjala et al. discloses that the IP telephony signaling protocol message is a message initiating a session [SIP or H.323, page 5, lines 32-33].
- 8. With regard to claim 3, Syrjala et al. discloses routing a call to the network node via an entry point [Fig. 1, GGSN]; and performing said adding in the entry point [GGSN transmits billing identifier, page 14, lines 7-14].
- 9. With regard to claim 4, Syrjala et al. discloses that the address of the entry point is added as service reference information to the IP telephony signaling protocol message [inherent because GPRS attachment has already occurred, page 13, lines 8-10; information for routing (IP address, page 13, line 22) to the access point is necessary for routing, page 13, lines 8-10].

10. With regard to claim 5, Syrjala et al. discloses that the service reference information is CAMEL-related information [CAMEL architecture, page 5, lines 7-9], the method further comprising the steps of:

routing a call to the network node via an entry point [Fig. 1, GGSN];
generating a CAMEL call reference number for the call in the entry point [GGSN]
generates the billing identifier, page 13, line 30], and

adding at least the CAMEL call reference number as said service reference information to the IP telephony signaling protocol message in the entry point [GGSN acknowledges the session by transmitting a response, page 14, lines 8-9].

11. With regard to claim 6, Syrjala et al. discloses that the service reference information is CAMEL-related information, the method further comprising the steps of:

routing a call to the network node via an entry point [Fig. 1, GGSN];

generating a CAMEL call reference number for the call in the entry point [GGSN generates the billing identifier, page 13, line 30]; and

coding the CAMEL call reference number and the address of the entry point to a digit string [integer plus address of particular network element, page 13, lines 30-36], and

adding at least the digit string as service reference information to the IP telephony signaling protocol message in the entry point [adding global billing identifier, page 13, line 30-36; the billing identifier is a new parameter, page 14, lines 9-10].

Art Unit: 2664

12. With regard to claim 7, Syrjala et al. discloses that the IP telephony signaling protocol message is a response message acknowledging a message invoking a session [GGSN acknowledges the session by transmitting a response, page 14, lines 8-9].

- 13. With regard to claim 8, Syrjala et al. discloses receiving an IP telephony signaling protocol message in a network node serving a called-subscriber [SIP or H.323, page 5, lines 32-33], and adding at least the address of said network node serving a called-subscriber as service reference information to the response message [inherent because GPRS attachment has already occurred, page 13, lines 8-10; information for routing (IP address, page 13, line 22) to the access point is necessary for routing, page 13, lines 8-10].
- 14. With regard to claim 9, Syrjala et al. discloses that the service reference information is CAMEL-related information [CAMEL architecture, page 5, lines 7-9] and said IP telephony signaling protocol message [SIP or H.323, page 5, lines 32-33] is a response message acknowledging a message invoking a session [GGSN acknowledges the session by transmitting a response, page 14, lines 8-9], the method further comprising the steps of:

receiving an IP telephony signaling protocol message invoking a session in a network node serving a called-subscriber [UE transmits message, page 13, lines 23-25],

generating a CAMEL call reference number for the call in said network node serving a called-subscriber [GGSN generates the billing identifier, page 13, line 30], and

Art Unit: 2664

adding at least the CAMEL call reference number as service reference information to the response message in said node serving a called subscriber [adding global billing identifier, page 13, line 30-36; the billing identifier is a new parameter, page 14, lines 9-10].

15. With regard to claim 10, Syrjala et al. discloses that the service reference information is CAMEL-related information [CAMEL architecture, page 5, lines 7-9] and said IP telephony signaling protocol message [SIP or H.323, page 5, lines 32-33] is a response message acknowledging a message invoking a session [GGSN acknowledges the session by transmitting a response, page 14, lines 8-9], the method further comprising the steps of:

receiving an IP telephony signaling protocol message in a network node serving a called subscriber [UE transmits message, page 13, lines 23-25],

generating a CAMEL call reference number for the call in said network node serving a called subscriber [GGSN generates the billing identifier, page 13, line 30],

coding the CAMEL call reference number and the address of said network node serving a called subscriber to a digit string [integer plus address of particular network element, page 13, lines 30-36], and

adding at least the digit string as service reference information to the response message [adding global billing identifier, page 13, line 30-36; the billing identifier is a new parameter, page 14, lines 9-10].

16. With regard to claim 11, Syrjala et al. discloses that the service reference information is OSA-related information [page 6, line 13].

Art Unit: 2664

17. With regard to claim 12, Syrjala et al. discloses that the service reference information is Parlay API-related information [page 6, line 13].

- 18. With regard to claim 13, Syrjala et al. discloses that the IP telephony signaling protocol is SIP [SIP or H.323, page 5, lines 32-33].
- 19. With regard to claim 14, Syrjala et al. discloses that the IP telephony signaling protocol is H.323 [SIP or H.323, page 5, lines 32-33].
- 20. With regard to claim 15, Syrjala et al. discloses serving a called subscriber with CAMEL-related information [CAMEL architecture, page 5, lines 7-9] in an IP-based system using SIP [SIP or H.323, page 5, lines 32-33], wherein the method comprises the steps of:

routing a call to the network node via an entry point for the called-subscriber [Fig. 1, GGSN],

generating a CAMEL call reference number for the call in the entry point [GGSN generates the billing identifier, page 13, line 30];

adding at least the CAMEL call reference number and the address of the entry point as CAMEL-related information to the SIP INVITE message [integer plus address of particular network element, page 13, lines 30-36], and

sending the SIP INVITE message to the network node [GGSN acknowledges the session by transmitting a response, page 14, lines 8-9].

Page 9

Art Unit: 2664

Application/Control Number: 09/835,821

21. With regard to claim 16, Syrjala et al. discloses a method for providing a network node serving a called-subscriber with CAMEL-related information [CAMEL architecture, page 5, lines 7-9] in an IP-based system using SIP [SIP or H.323, page 5, lines 32-33], wherein the method comprises the steps of:

routing a call to the network node via an entry point for the called-subscriber [Fig. 1, GGSN],

generating a CAMEL call reference number for the call in the entry point [GGSN generates the billing identifier, page 13, line 30];

coding the CAMEL call reference number and the address of the entry point in a digit string, adding at least the digit string as CAMEL-related information to the SIP INVITE message [integer plus address of particular network element, page 13, lines 30-36], and

sending the SIP INVITE message to the network node [GGSN acknowledges the session by transmitting a response, page 14, lines 8-9].

22. With regard to claim 17, Syrjala et al. discloses a method for providing an IP-based system using SIP [SIP or H.323, page 5, lines 32-33] with CAMEL-related information [CAMEL architecture, page 5, lines 7-9], wherein the method comprises the steps of:

receiving a SIP INVITE message a network node serving a called-subscriber from an entry point for the called-subscriber [Fig. 1, GGSN];

generating a CAMEL call reference number for the call in the network node [GGSN generates the billing identifier, page 13, line 30];

Art Unit: 2664

adding at least the CAMEL call reference number and the address of the network node as CAMEL-related information to a SIP response message acknowledging SIP INVITE message [integer plus address of particular network element, page 13, lines 30-36], and

sending the SIP response message to the entry point [GGSN acknowledges the session by transmitting a response, page 14, lines 8-9].

23. With regard to claim 18, Syrjala et al. discloses a method for providing an IP-based system using SIP [SIP or H.323, page 5, lines 32-33] with CAMEL-related information [CAMEL architecture, page 5, lines 7-9], wherein the method comprises the steps of:

receiving a SIP INVITE message a network node serving a called subscriber from an entry point for the called subscriber [Fig. 1, GGSN],

generating a CAMEL call reference number for the call in the network node [GGSN generates the billing identifier, page 13, line 30];

coding the CAMEL call reference number and the address of the network node in a digit string; adding the digit string and CAMEL-related information to a SIP response message [integer plus address of particular network element, page 13, lines 30-36] acknowledging the SIP INVITE message [GGSN acknowledges the session by transmitting a response, page 14, lines 8-9], and

adding the SIP response message to the entry point [adding global billing identifier, page 13, line 30-36; the billing identifier is a new parameter, page 14, lines 9-10].

Art Unit: 2664

24. With regard to claim 21, Syrjala et al. discloses a communications system providing IP

telephony, comprising at least

user equipment [Fig. 1, UE],

a first network node [Fig. 1, GGSN], and

a second network node [Fig. 1, SGSN],

wherein the first network node is arranged to add service reference information relating

to a call made to the user equipment [adding global billing identifier, page 13, line 30-36; the

billing identifier is a new parameter, page 14, lines 9-10] to an IP telephony signaling protocol

message [SIP or H.323, page 5, lines 32-33] and to send the IP telephony signaling protocol

message to the second network node [page 14, lines 8-10]; and

the second network node is arranged to separate the service reference information from

the IP telephony signaling protocol message [SGSN separates the billing identifier from the

message, page 14, lines 10-11].

25. With regard to claim 22, Syrjala et al. discloses a communications system according to claim

21, wherein the first network node is arranged to add its address as service reference information

to the IP telephony signaling protocol message [integer plus address of particular network

element, page 13, lines 30-36].

26. With regard to claim 23, Syrjala et al. discloses a communications system according to claim

21, wherein the communications system provides a CAMEL service [CAMEL architecture,

page 5, lines 7-9]; and

Art Unit: 2664

the first network node is arranged to generate a CAMEL call reference number and to add at least the generated CAMEL call reference number as service reference information to the IP telephony signaling protocol message [GGSN generates the billing identifier, page 13, line 30; adding integer plus address of particular network element, page 13, lines 30-36].

27. With regard to claim 24, Syrjala et al. discloses a communications system using SIP for IP telephony and providing a CAMEL service [CAMEL architecture, page 5, lines 7-9], comprising at least

user equipment [Fig. 1, UE],

a first network node [Fig. 1, GGSN], and

a second network node [Fig. 1, SGSN],

wherein the first network node is arranged to add CAMEL-related information relating to a call made to the user equipment [adding global billing identifier, page 13, line 30-36; the billing identifier is a new parameter, page 14, lines 9-10] to a SIP message [SIP or H.323, page 5, lines 32-33] and to send the SIP message to the second network node [page 14, lines 8-10]; and

the second network node is arranged to separate the CAMEL-related information from the SIP message [SGSN separates the billing identifier from the message, page 14, lines 10-11].

Art Unit: 2664

lines 30-36].

28. With regard to claim 25, Syrjala et al. discloses that the first network node is arranged to generate a CAMEL call reference number [GGSN generates the billing identifier, page 13, line 30] and to add at least the CAMEL call reference number and its address as CAMEL-related information to the SIP message [integer plus address of particular network element, page 13,

- 29. With regard to claim 26, Syrjala et al. discloses that the first network node is arranged to generate a CAMEL call reference number [GGSN generates the billing identifier, page 13, line 30], to code at least the CAMEL call reference number and its own address to a digit string and to add at least the digit string as CAMEL-related information to the SIP message [integer plus address of particular network element, page 13, lines 30-36], and the second network node is arranged to decode the digit string [SGSN separates the billing identifier from the message, page 14, lines 10-11].
- 30. With regard to claim 29, Syrjala et al. discloses a communications system providing IP telephony, comprising at least

user equipment [Fig. 1, UE],

a first network node [Fig. 1, SGSN], and

a second network node [Fig. 1, GGSN],

wherein the first network node [Fig. 1, SGSN] is arranged

Art Unit: 2664

to add first service reference information relating to a call made to the user equipment to an IP telephony signaling protocol message initiating a session, to send the IP telephony signaling protocol message initiating a session to the second network node [SGSN adds the address of the GGSN in order to contact GGSN to request a session, page 13, lines 27-30],

to receive a response message acknowledging the IP telephony signaling protocol message initiating a session and to separate second service reference information relating to the call from the SIP response message [GGSN generates the billing identifier, page 13, line 30, GGSN acknowledges the session by transmitting a response including the billing identifier, page 14, lines 8-9], and

the second network node [Fig. 1, GGSN] is arranged

to separate the first service reference information from the IP telephony signaling protocol message initiating a session [GGSN is addressed and a session is requested, page 13, lines 27-30],

to add the second service reference information to the response message and to send the response message to the first network node [GGSN generates the billing identifier, page 13, line 30, GGSN acknowledges the session by transmitting a response including the billing identifier, page 14, lines 8-9].

31. With regard to claim 30, Syrjala et al. discloses a communications system using SIP for IP telephony and providing a CAMEL service, comprising at least user equipment [Fig. 1, UE],

Art Unit: 2664

a first network node [Fig. 1, SGSN], and
a second network node [Fig. 1, GGSN],
wherein the first network node [Fig. 1, SGSN] is arranged

to add first CAMEL-related information relating to a call made to the user equipment to a SIP INVITE message, to send the SIP INVITE message to the second network node [SGSN adds the address of the GGSN in order to contact GGSN to request a session, page 13, lines 27-30],

to receive a SIP response message acknowledging the SIP INVITE message and to separate second CAMEL-related information relating to the call from the SIP response message [GGSN generates the billing identifier, page 13, line 30, GGSN acknowledges the session by transmitting a response including the billing identifier, page 14, lines 8-9], and

the second network node [Fig. 1, GGSN] is arranged

to separate the first CAMEL-related information from the SIP INVITE message [GGSN is addressed and a session is requested, page 13, lines 27-30],

to add the second CAMEL-related information to the SIP response message and to send the SIP response message to the first network node [GGSN generates the billing identifier, page 13, line 30, GGSN acknowledges the session by transmitting a response including the billing identifier, page 14, lines 8-9].

32. With regard to claim 31, Syrjala et al. discloses that the first CAMEL-related information includes at least the address of the first network node [SGSN adds the address of the GGSN in order to contact GGSN to request a session, page 13, lines 27-30], the second network node is further arranged to generate a CAMEL call reference number; and the second CAMEL-related information includes at least the CAMEL call reference number [GGSN generates the billing identifier, page 13, line 30, GGSN acknowledges the session by transmitting a response including the billing identifier, page 14, lines 8-9].

- 33. With regard to claim 32, Syrjala et al. discloses that the first network node is further arranged to generate a CAMEL call reference number, and the first CAMEL-related information includes at least the generated CAMEL call reference number, and the second CAMEL-related information includes at least the address of the second network node [the call can be started in the opposite direction, and the SGSN can also generate the billing identifier, page 17, lines 13-15].
- 34. With regard to claim 33, Syrjala et al. discloses a network node [Fig. 1, GGSN] in a communications system providing IP telephony, wherein the network node comprises means for adding service reference information to an IP telephony signaling protocol message [GGSN generates the billing identifier, page 13, line 30, GGSN acknowledges the session by transmitting a response including the billing identifier, page 14, lines 8-9].

Page 17

Application/Control Number: 09/835,821

Art Unit: 2664

- 35. With regard to claim 34, Syrjala et al. discloses a network node [Fig. 1, SGSN] in a communications system providing IP telephony, wherein the network node comprises means for separating service reference information from an IP telephony signaling protocol message [SGSN separates the billing identifier from the message, page 14, lines 10-11].
- 36. With regard to claim 35, Syrjala et al. discloses a network node [Fig. 1, GGSN] in a communications system using SIP [SIP or H.323, page 5, lines 32-33] and providing a CAMEL service [CAMEL architecture, page 5, lines 7-9], wherein the network node comprises means for adding CAMEL-related information to a SIP message [GGSN generates the billing identifier, page 13, line 30, GGSN acknowledges the session by transmitting a response including the billing identifier, page 14, lines 8-9].
- 37. With regard to claim 36, Syrjala et al. discloses a network node [Fig. 1, GGSN] in a communications system using SIP [SIP or H.323, page 5, lines 32-33] and providing a CAMEL service [CAMEL architecture, page 5, lines 7-9], wherein the network node comprises means for generating a CAMEL call reference number and means for adding at least the CAMEL call reference number as CAMEL-related information to a SIP message [GGSN generates the billing identifier, page 13, line 30, GGSN acknowledges the session by transmitting a response including the billing identifier, page 14, lines 8-9].

Claim Rejections - 35 USC § 102/103

38. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness

rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person

such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the

manner in which the invention was made.

39. Claims 19-20, 27-28, and 37-43 are rejected under 35 U.S.C. 102(e) as being anticipated by

Syrjala et al. (WO 01/91445). In the alterative, claims 19-20, 27-28, and 37-43 are rejected under

35 U.S.C. 103(a) as being unpatentable over Syrjala et al. (WO 01/91445).

40. With regard to claim 37, Syrjala et al. discloses that the network node comprises a call state

control function. It is inherent that a gateway support node would comprise a call state control

function. In the alternative, such a functionality is well-known in the art. Thus, it would have

been obvious to one of ordinary skill in the art at the time of the invention to have incorporated a

call state control function because such functionality would provide the node the means to

control calls and use it to control the billing associated with each user terminal with regard to the

individual billing identifiers, in order to charge the appropriate accounts fairly.

41. With regard to claims 19-20, 27-28, and 38-43, it is inherent that the billing identifier would

be added to either the packet header or payload (body) for a packet standard [e.g., SIP] that does

not include such information but must be transferred with that packet/protocol. In the

alternative, placing specific information such as a billing identifier in either a packet header or

payload would have been obvious to one of ordinary skill in the art at the time of the invention

Art Unit: 2664

because such information, in the event of a system which requires it, would have to be placed in

an adapted packet/protocol in order to transport and signal with such information that is critical

to system operation (e.g., correct billing information).

Conclusion

42. Any inquiry concerning this communication or earlier communications from the examiner

should be directed to Mark A. Mais whose telephone number is (571) 272-3138. The examiner

can normally be reached on 6:00-4:30.

43. If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor,

Wellington Chin can be reached on (571) 272-3134. The fax phone number for the organization

where this application or proceeding is assigned is 571-273-8300.

44. Information regarding the status of an application may be obtained from the Patent

Application Information Retrieval (PAIR) system. Status information for published applications

may be obtained from either Private PAIR or Public PAIR. Status information for unpublished

applications is available through Private PAIR only. For more information about the PAIR

system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR

system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

September 20, 2005

WELLINGTON CHIN RVISORY PATENT EXAMIN"

Page 19